

Quotation Request //

US Government Printing Office

Atlanta Regional Office
1888 Emery St., Suite 110
Atlanta GA 30318-2566

JACKET:524-923 R-1

Quotations are Due By:

(Eastern Time) 11:00 AM on 04/30/2009

Submit Fax Quotes to: (404) 605-9185

Contractors must provide mandatory taxpayer information before GPO makes payment.

Please see special notice on <http://contractorconnect.gpo.gov/>.

TITLE: PATIENT TREATMENT CHART

QUANTITY: 300 File Folders

REPOSTED / BID OPENING DATE & OPENING TIME HAVE CHANGED

Revision # 1

TRIM SIZE: 43-3/16 x 11" flat; 8-15/16 x 11" folded

PAGES: Face and back

SCHEDULE:

Furnished Material will be available for pickup by 04/30/2009

Deliver complete (to arrive at destination) by 05/11/2009

F.O.B. destination

QUALITY LEVEL: 3 Quality Assurance Through Attributes (GPO PUB 310.1, effective May 1979 (Rev. 8-02)) applies.

DESCRIPTION:

File folders print type, lines and screen matter in black ink. Ink coverage 60%, no bleeds.

MATERIAL FURNISHED: Contractor to pickup at GPO. .

- One previous printed sample to be used as stock likeness (weight/finish), margin, prong fastener placement and construction guide.

- 8 single piece (9 x 11-1/2") negatives. Contractor to strip, register and opaque negatives as necessary.

NOTE: Negatives must be removed from all flats prior to returning GFM.

PAPER: * Must be in accordance with JCP Paper Specification Standards in effect on date of this order
JCP Code* P20, High-Finish Folder Stock, White*, Basis Size 24 X 36", Thickness .012"

*NOTE: Previous printed sample to be used for stock likeness (weight/finish)

COLOR OF INK: Ink Must Contain a Minimum of 20% Vegetable Oil

Black

PRINT PAGE: Head to Head

MARGINS:

- Follow copy sample, adequate gripper.

BINDING:

- Fasteners: 1 leaf (panel 3) to be equipped with a permanently affixed, prong type, one piece, rust resistant metal fastener, similar to Acco or other fastener of similar design and equal quality and durability which meet the following requirements.

a. Quality of metal: Fastener to be made of corrosion resistant, plated, bright finish metal or baked enamel finished metal, 0.33 mm (0.013") plus/minus 0.03 mm (0.001") thickness, Rockwell Hardness F-79 to F-89

and to be of such ductility that it will withstand a minimum of 20 ninety-degree flexing cycles without fracture.

Bend Test: With the fasteners in the normal flat position, bend the prongs to a vertical position, insert one sheet of punched paper on the prongs and bend the prongs back to the flat position. Continue this cycle of bends a minimum of 20 times, taking not less than 1 minute to complete the 20 cycles.

b. Prongs: Width $7/32$ "; Length $2-1/4$ "; Spaced $2-3/4$ " center-to-center.

c. The fasteners shall be produced with properly maintained dies to insure that the finished product is free from burrs, sharp edges, cracks, flaws, and malformations which may cause injury to personnel or damage to the filed papers. The fasteners shall be free from oil or grease.

d. Acco type, or equal, fasteners to be securely affixed to the folder with a permanent type adhesive which will permanently bond the fastener, remain flexible for the life of the folder and not permit fungus or algae growth. Prongs to be one continuous piece. Folder leaf is not die-cut or embossed.

e. One fastener to be positioned (prongs inside) as follows:

(1) One at the top of the inside front leaf (panel 2), center of fastener $3/4$ " from top edge and $4-5/16$ " from the fold.

- Drill 2 round holes $1/4$ " in diameter, $2-1/4$ " center-to-center, centered on the top $8-7/8$ " dimension (panel 2-see sample). Center of holes $7/16$ " from the top edge of sheet.

- Score in four (4) locations along the entire 11" dimension, $8-15/16$ ", $17-13/16$ ", $26-3/8$ ", and $34-7/8$ " in from left edge of sheet.

- Fold from $43-3/16 \times 11$ " to $8-15/16 \times 11$ " via four parallel, wrap-around folds, face panel out.

PACKING:

- Pack suitable per shipping container*.

*NOTE: All shipping containers require a container label. Complete a copy of the enclosed shipping label(s) and affix one to each shipping container according to the instruction at the top of the carton label sheet (make additional copies as necessary). There will be a minimum charge of \$50.00 per order (per Jacket) for all labeling and marking corrections that are made by the Government due to the contractor's failure to label/mark all containers per specifications and Contract Terms.

DISTRIBUTION:

Deliver all copies to:

VAMC/Radiation Therapy/586-P94799, 1500 East Woodrow Wilson, Jackson, MS 39216---Attn: Tonia Green / Betty Hall (601) 362-4471, ext. 5735/4485.

Return all furnished material, and negative(s) under separate cover (appropriately identified) by traceable means to:

VAMC/Radiation Therapy/586-P94799, 1500 East Woodrow Wilson, Jackson, MS 39216---Attn: Tonia Green / Betty Hall (601) 362-4471, ext. 5735/4485.

QUALITY ASSURANCE LEVELS AND STANDARDS: The following levels and standards shall apply to these specifications:

Inspection Levels (from ANSI/ASQC Z1.4):

(a) Non-destructive Tests -- General Inspection Level I.

(b) Destructive Tests -- Special Inspection Level S-2.

Specified Standards-- The specified standards for the attributes requiring them shall be:

ATTRIBUTE

SPECIFIED STANDARD

P-7. Type Quality and Uniformity

Government Furnished Negs.

DISPUTES CLAUSE: GPO Publication 310.2, GPO Contract Terms, Contract Clause 5. Disputes, is hereby replaced with the June 2008 clause found at www.gpo.gov/printforms/pdf/contractdisputes.pdf. This June 2008 clause also cancels and supersedes any other disputes language currently included in existing contractual actions.

All GPO publications referenced in these specifications are available on the internet via the GPO web-site, <http://www.contractorconnect.gpo.gov>.